

Applications

- For use with gasoline, diesel, biodiesel blends up to B20, or ultra-low sulfur diesel (ULSD)
- For use on:
 - Aboveground storage tanks
 - Transfer tanks
 - Day-use tanks
- Gravity flow applications, transfer pumps & fuel dispensers

Benefits & Design Features

- Up to 25 gpm (94.6 lpm) maximum flow
- 50 psi (3.4 bar) maximum working pressure
- Various micron media(s) available
- Pre-Lubed gaskets
- Removes common contaminants such as dirt, dust, and rust
- Drain for easy water removal

200E Series

3¾" x 8" x 1"-12 Thread

200AE Series

3¾" x 8" x 1⅜"-12 Thread

250E Series

3¾" x 7¼" x 1"-12 Thread

250AE Series

3¾" x 7¼" x 1⅜"-12 Thread



NOT FOR AVIATION USE

Cellulose with Drain

Part #	Model #	Micron	Function	Fuel
70002	200E-10	10	Particulate Removal	Gasoline, diesel, biodiesel, ULSD
70046	200E-30	30	Particulate Removal	Gasoline, diesel, biodiesel, ULSD
70004	200AE-10	10	Particulate Removal	Gasoline, diesel, biodiesel, ULSD
70045	200AE-30	30	Particulate Removal	Gasoline, diesel, biodiesel, ULSD

Cellulose without Drain

Part #	Model #	Micron	Function	Fuel
70819	250E-02	2	Particulate Removal	Gasoline, diesel, biodiesel, ULSD
70003	250E-10	10	Particulate Removal	Gasoline, diesel, biodiesel, ULSD
70821	250AE-02	2	Particulate Removal	Gasoline, diesel, biodiesel, ULSD
70005	250AE-10	10	Particulate Removal	Gasoline, diesel, biodiesel, ULSD
70089	250AE-30	30	Particulate Removal	Gasoline, diesel, biodiesel, ULSD

Mounting Adaptors

Part #	Material	Fuel Ports	Thread	Use With
50003	Cast Iron	¾" NPT	1"-12	200E & 250E
50002	Cast Iron	1" NPT	1"-12	200E & 250E
50004	Cast Iron	1" NPT	1⅜"-12	200AE & 250AE
50181	Aluminum	¾" NPT	1"-12	200E & 250E

Replacement Gaskets

Part #	Description
90025	Buna-N Pre-Lubed Gasket